

# Halogen reflector

# 13194 85W GX5.3 13.8V 1CT

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 - the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

## Product data

#### • General Characteristics

Philips Code 13194 ANSI Code DED I Code LIF Code Cap-Base GX5.3 Cap-Base Information Bulb R50 Bulb Material Quartz-UV Open Reflector Finish Smooth Filament Shape Operating Position s105 Main Application Projection Life to 50% failures 1000 hr For professional use only-not for Non-household Symbol domestic use

#### • Light Technical Characteristics

| Color Rendering    | 100 Ra8 |
|--------------------|---------|
| Index              |         |
| Color Temperature  | 3150 K  |
| Technical          |         |
| Luminous Flux Lamp | 2066 Lm |
|                    |         |

#### • Electrical Characteristics

| Lamp Wattage | 85 W   |
|--------------|--------|
| Voltage      | 13.8 V |
| Lamp Voltage | 13.8 V |
| Dimmable     | Yes    |
|              |        |

#### Luminaire Design Requirements

| Pinch Temperature | 350 (max) C |
|-------------------|-------------|
| Bulb Temperature  | 900 (max) C |
| Working Distance  | 165 mm      |
| WD                |             |

#### Product Dimensions

Overall Length C 45 (max) mm Diameter D 50 (max) mm Filament Dimensions (WxH) [mm]

#### • Product Data

Order code Full product code Full product name Order product name Pieces per pack Packing configuration Packs per outerbox 50 Bar code on pack -EAN1 Bar code on intermediate packing -EAN2 Bar code on outerbox - EAN3 Logistic code(s) -12NC Net weight per piece


923883618204 923883618204 13194 85W GX5.3 13.8V 1CT 13194 85W GX5.3 13.8V 1CT/10X5F 10X5F 8711500409720 8711500419262 8711500419255 923883618204

0.026 kg



# Halogen reflector

### Dimensional drawing





GX5.3

# PHILIPS

 $\textcircled{\sc c}$  2015 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

| Product               | C (Max) | D (Max) | L (Min) | L (Norm) | L (Max) |
|-----------------------|---------|---------|---------|----------|---------|
| 13194 85W GX5.3 13.8V | 45      | 50      | -       | -        | -       |