# TL 100W/10-R UV-A

Flexo print TL lamps emit almost all of their light (99.9%) in the useful UVA and visible blue wavebands – between 350 and 400 nm – and have peak intensity at 370 nm (except for the /03 version). This makes them ideal for flexo printing equipment and photopolymerization processes. In addition, the 'R' lamps in the family have an internal 200-degree reflector to further optimize the lamp's overall efficiency.



### Product data

### General Characteristics

Cap-Base G13
Bulb T38
Main Application Phototherapy
Useful Life 1000 hr
Life to 50% failures 2000 hr

EΜ

### • Light Technical Characteristics

Color Code Color Designation Ultra Violet A (text) Chromaticity Coor-220 dinate X Chromaticity Coor-200 dinate Y Depreciation 500 10 % hours Depreciation 1000 20 % hours Depreciation 2000 30 % hours


### • Electrical Characteristics

Lamp Wattage 100 W
Lamp Wattage Technical
Lamp Voltage 122 V
Lamp Current 0.97 A

#### • Environmental Characteristics

Mercury (Hg) 13.0 mg Content

# Dimensional drawing



# • UV-related Characteristics

UV-A Radiation 26.0 W 100hr (IEC) 0.1 % UV-B/UV-A (IEC) 0.1 % UV-A Radiation 0hr (IEC)

### • Product Dimensions

Base Face to Base 1763.8 (max) mm
Face A
Insertion Length B 1768.5 (min), 1770.9 (max) mm
Overall Length C 1778 (max) mm
40.5 (max) mm

### • Product Data

928006901029 Order code 928006901029 Full product code TL 100W/10-R UV-A Full product name Order product name TL 100W/10-R UV-A Pieces per pack
Packing configuration 25 Packs per outerbox 25 8711500612816 Bar code on pack -EAN1 Bar code on 8711500612823 outerbox - EAN3 928006901029 Logistic code(s) -12NC Net weight per piece 391.600 gr

### TL 100W/10-R UV-A

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL 100W UV-A 1R	1763.8	1768.5	1770.9	1778	40.5

# Dimensional drawing



G13

# Photometric data

